Blink

protegge le superfici delle pietre arenarie e calcaree

Scheda Tecni

CARATTERISTICHE

- Blink, formulazione a base acqua, penetra nel materiale attraverso le porosità creando una pellicola protettiva invisibile.
- Impedisce allo sporco di penetrare nei materiali trattati.
- Le superfici trattate con Blink si puliscono facilmente.
- Consolida il materiale migliorando la resistenza al calpestio.
- L'applicazione del prodotto rende la pietra impermeabile.

CAMPI D'APPLICAZIONE

Blink è un prodotto adatto al trattamento delle pietre arenarie e calcaree (sandstone e limestone).

E' particolarmente indicato per la protezione di pavimenti, scale e rivestimenti interni.

MODO D'USO

- Applicare Blink a rullo a pelo raso o pennello, fino a saturazione del supporto.
- Lasciare assorbire.
- Dopo pochi minuti ripulire eventuali residui con un panno,anche di microfibra, inumidito con un po di Blink senza esercitare troppa pressione sulla superficie.
- Lasciare asciugare almeno 2-3 ore prima della manipolazione, e almeno 24 ore prima della messa in uso della superficie trattata.
- Ripetere l'applicazione se necessario.

RESA

7 - 15 m2/ kg

AVVERTENZE

La buona riuscita del trattamento dipende da una corretta applicazione.

Si consiglia, se necessario, l'applicazione di una seconda mano. È possibile diluire Blink con acqua in base alle caratteristiche del materiale da trattare (massimo 20 - 30% di acqua).

ETICHETTATURA e SICUREZZA

Blink è un prodotto chimico.
Per informazioni sull' etichettatura e i rischi connessi alla manipolazione e all'uso del prodotto consultare la Scheda di Sicurezza. Se non è stata ricevuta, essa è disponibile a richiesta presso Industrial Chem Italia.

STOCCAGGIO

Blink chiuso e sigillato nei suoi contenitori originali, conservato a una temperatura tra i 5 e i 30 °C lontano da fonti di calore e protetto dalla luce solare diretta, ha una durata di 12 mesi.

RESPONSABILITA'

Tutte le informazioni e raccomandazioni qui contenute, sono basate su informazioni e test che riteniamo attendibili; non conoscendo tuttavia le condizioni circa i materiali trattati e le modalità di messa in opera in cui il prodotto viene utilizzato, si declina ogni responsabilità circa l'adeguatezza del prodotto per ogni particolare applicazione. È infatti compito dell'utilizzatore verificare, sotto la propria responsabilità, se il prodotto descritto si presta in maniera appropriata all'uso a cui è destinato, e di procedere a tutte le prove preliminari necessarie, comprese quelle legate all'utilizzo di macchine o strumenti di lavoro.



rev. settembre 2021



AZIENDA CON
SISTEMA DI GESTIONE
CERTIFICATO DA DNV
ISO 9001 • ISO 14001

INDUSTRIAL CHEM ITALIA s.r.l.
www.industrialchemitalia.com
Tel. +39 0584 969 607
commerciale@industrialchemitalia.com

BLINK

total protection for limestone and sandstone floors

Technical She

PROPERTIES

- Blink, a water-based formulation, penetrates the material through porosities creating an invisible protective film.
- Prevents dirt from penetrating into the treated materials.
- Surfaces treated with Blink are easy to clean.
- Consolidates the material by improving resistance to foot traffic (trampling).
- Applying the product makes the stone waterproof.

APPLICATION FIELD

Blink is a product suitable for the treatment of sandstone and limestone.

It is particularly suitable for the protection of floors, stairs and interior coverings.

INSTRUCTION FOR USE

- Apply Blink with a short hair roller or brush, until the substrate is saturated.
- Let it absorb.
- After a few minutes, clean up any residues with a cloth, even microfibre, moistened with a little Blink without exerting too much pressure on the surface.
- Allow to dry at least 2-3 hours before handling, and at least 24 hours before putting the treated surface into use.
- Repeat the application as needed.

YELD

7 - 15 m2/ kg



USEFUL RECOMMENDATIONS

The success of the treatment depends on a correct application.

If necessary, a second coat is recommended. It is possible to dilute Blink with water according to the characteristics of the material to be treated (maximum 20 - 30% of water).

SAFETY & LABELING

Blink is a chemical product.
For information concerning labeling, handling and utilization risks , please read the Material Safety Data Sheet. If this has not been received, it can be requested to: export@industrialchemitalia.com.

STORAGE

Blink properly stored in the original unopened containers, at a temperature between 5 - 30°C, far from direct sunlight and other heat sources has a shelf life of 12 months.

RESPONSIBILITY

All the data and recommendations hereby contained, are based on reliable tests and informations. However being unaware of the conditions of the materials that are going to be treated as well as the modalities of application that are going to be used, our company doesn't assume any kind of resposability. It is up to the user to determine, under its full responsibility, whether this specific product is suitable for the proposed use and to perform all preliminary tests, including those related to the use of machines and tools.

rev. september 2021

COMPANY WITH
MANAGEMENT SYSTEM
CERTIFIED BY DNV
ISO 9001 • ISO 14001



INDUSTRIAL CHEM ITALIA s.r.l.
www.industrialchemitalia.com
Tel. +39 0584 969 607
export@industrialchemitalia.com