New Microkem Dc8

intensifica il colore dei graniti e dei marmi lucidi e colorati

Scheda Tecni

CARATTERISTICHE

- New Microkem DC8 migliora il lucido e intensifica il colore di marmi e graniti
- Elimina le magrosita dai graniti
- Conferisce idrorepellenza ai materiali trattati proteggendo a lungo le superfici dall'azione di piogge acide , raggi UV , smog e dall'aggressione di microrganismi.
- Certificato idoneo per il contatto alimentare anche con l' aggiunta dei pigmenti coloranti Up Grade.
- Non crea pellicola superficiale.
- New Microkem DC8 può essere applicato neutro o dove necessario, aggiungendo i pigmenti coloranti Up Grade, da noi studiati e selezionati per la loro atossicità, stabilità .e durata.nel tempo.
- New Microkem DC8 + UP Grade, modificano in maniera permanente il tono di colore e la qualità delle superfici dei materiali trattati.

CAMPI D'APPLICAZIONE

New Microkem Dc8 si utilizza su marmi e graniti colorati, carenti di lucido e inadeguata colorazione naturale .

Tonalizza e protegge materiali quali Pietra Serena, Quarziti Indiane, Brasiliane e Cardoso. Esalta la colorazione dei Quarzi resina opacizzati dall'aggressione dei raggi UV

New Microkem Dc8 è particolarmente idoneo quale idrorepellente per agglomerati cementizi, pannelli in cemento armato e calcestruzzo. Evita il dilavamento del colore originale dei manufatti causato dal PH acido insito nei composti del cemento.

Idoneo per piani di cucina , tavoli , banchi bar ecc.

MODO D'USO

Applicare New Microkem DC8 neutro o con l' aggiunta dei pigmenti coloranti Up Grade, su superfici asciutte, pulite, non resinate e non precedentemente trattate con prodotti chimici.

Manuale su manufatti e lastre

- Versare sulla superficie da trattare piccole quantità di New Microkem Dc8 e uniformare con pannocarta tipo Scottex.
- Lasciare agire alcuni secondi, utilizzare pannocarta tipo Scottex asciutta per togliere i residui di colore e tirare il prodotto.



rev. settembre 2021

- Lucidare con un panno di microfibra.

Automatico su lastre lucide

- Applicare il il prodotto in linea utilizzando una macchina ceratrice

RESA

GRANITI E MARMI

Manuale: 30 - 40 m2/ lt
Automatico: 60 - 100 m/ lt

PIETRE

12 - 20 m2/ lt

QUARZO RESINA

50 - 80 m/ lt

PER AGGLOMERATI DI CEMENTO CEMENTO ARMATO E CALCESTRUZZO

5 - 15 m2/ lt

AVVERTENZE

Si sconsiglia l'utilizzo sui materiali bianchi, fatta esclusione per gli agglomerati di cemento.
Per maggiori informazioni sull'utilizzo dei pigmenti Up Grade consultare la scheda tecnica.

ETICHETTATURA e SICUREZZA

New Microkem Dc8 è un prodotto chimico.
Per informazioni sull' etichettatura e i rischi connessi alla manipolazione e all'uso del prodotto consultare la Scheda di Sicurezza. Se non è stata ricevuta, essa è disponibile a richiesta presso Industrial Chem Italia.

STOCCAGGIO

New Microkem Dc8 chiuso e sigillato nei suoi contenitori originali, conservato a una temperatura tra i 5 e i 30 °C lontano da fonti di calore e protetto dalla luce solare diretta, ha una durata di 24 mesi.

RESPONSABILITA'

Tutte le informazioni e raccomandazioni qui contenute, sono basate su informazioni e test che riteniamo attendibili; non conoscendo tuttavia le condizioni circa i materiali trattati e le modalità di messa in opera in cui il prodotto viene utilizzato, si declina ogni responsabilità circa l'adeguatezza del prodotto per ogni particolare applicazione. È infatti compito dell'utilizzatore verificare, sotto la propria responsabilità, se il prodotto descritto si presta in maniera appropriata all'uso a cui è destinato, e di procedere a tutte le prove preliminari necessarie, comprese quelle legate all'utilizzo di macchine o strumenti di lavoro.



AZIENDA CON
SISTEMA DI GESTIONE
CERTIFICATO DA DNV
ISO 9001 • ISO 14001

INDUSTRIAL CHEM ITALIA s.r.l.
www.industrialchemitalia.com
Tel. +39 0584 969 607
commerciale@industrialchemitalia.com

New Microkem Dc8

enhancer water repellent for polished marbles and granites

technical she

PROPERTIES

■New Microkem Dc8 is a chemical with really special and unique properties.
■It is very easy to use, dries in less than 30 seconds and improves permanently the appearence of marble and granites.
■ Can be used transparent to enhance polish and tone, or with pigments Up Grade to give stronger effect.
■In addition the surface will be protected from dust and water absorption. If not abraded, will last many many years in place.
■ Above all, makes the surface suitable for Food Contact.

APPLICATION FIELD

New Microkem Dc8 is used on marbles and granites, lacking in gloss and inadequate natural color.

It tones and protects also materials such as Pietra Serena, Indian and Brazilian Quartzites. It enhances the coloring of resin quartz opaqued by the aggression of UV rays
New Microkem Dc8 is particularly suitable as water repellent for cement agglomerates, reinforced concrete panels and concrete. It avoids the leaching of the original color of the artifacts caused by the acid PH inherent in the cement compounds.

Suitable for kitchen tops, tables, bar counters etc.erates.

INSTRUCTIONS FOR USE

Apply New Microkem Dc8, neutral or with the addition of Up Grade pigments, on clean dry surfaces, not resinate and not previously treated with other chemicals.

Manual application on artifacts and polished slabs

- Pour small quantities of New Microkem Dc8 onto the surface to be treated and even out with kitchen paper towel.
- Leave to act for a few seconds and use dry kitchen paper to remove color residues.
- Polish with a microfibre cloth.



rev. september 2021

Automatic application on polished slabs

- Apply the product using the wax machine

YIELD

marbles and granites:

Manual: 30 - 40 m2/ lt
Automatic: 60 -100 m2/ lt
stones:

10 - 20 m2 / lt

quartz resin:

50 - 80 m2 / lt

agglomerates of concrete cement and concrete:

5-15 m2/lt

USEFUL RECOMMENDATIONS

New Microkem Dc8 is not recommended for use on white materials, except for concrete conglomerates.
For more information about the use of Up Grade pigments, see the technical data sheet.

SAFETY & LABELING

New Microkem Dc8 is a chemical product.
For information concerning labeling, handling and utilization risks , please read the Material Safety Data Sheet. If this has not been received, it can be requested to: export@industrialchemitalia.com

STORAGE

New Microkem DC8 properly stored in the original unopened containers, at a temperature between 5 - 30°C, far from direct sunlight and other heat sources has a shelf life of 24 months.

RESPONSIBILITY

All the data and recommendations hereby contained, are based on reliable tests and informations. However being unaware of the conditions of the materials that are going to be treated as well as the modalities of application that are going to be used, our company doesn't assume any kind of resposability. It is up to the user to determine, under its full responsibility, whether this specific product is suitable for the proposed use and to perform all preliminary tests, including those related to the use of machines and tools.



COMPANY WITH MANAGEMENT SYSTEM CERTIFIED BY DNV
ISO 9001 • ISO 14001

INDUSTRIAL CHEM ITALIA s.r.l.
www.industrialchemitalia.com
Tel. +39 0584 969 607
export@industrialchemitalia.com