Stain Out

rimuove macchie d'olio e grasso dalle pietre naturali

scheda tecnic

CARATTERISTICHE

- Stain Out è un formulato speciale che grazie alla sua azione penetra nei materiali e rimuove macchie di grasso, cera, olio minerale e vegetale.
- Stain Out è di facile impiego, assorbe le macchie in pochi minuti e le asporta.
- Stain Out non lascia aloni e non altera il colore dei materiali trattati
- È possibile eseguire applicazioni localizzate del prodotto grazie alla sua formulazione cremosa.

CAMPI D'APPLICAZIONE

Stain Out è adatto per tutte le superfici lucide, levigate, grezze, patinate, ecc. È indicato per tutti i tipi di materiali lapidei, per il cotto, ecc.

MODO D'USO

Agitare bene il prodotto prima dell'utilizzo.

- Applicare Stain Out sulla macchia, ricoprendola interamente, creando uno strato di prodotto di almeno 5 mm.
- Se necessario ricoprire la superficie con film plastico per alimenti.
- Lasciare asciugare fintanto che la superficie diventi secca e crepata.
- Rimuovere il residuo con una spatola.
- Ripetere se necessario l'operazione.

AVVERTENZE

Dopo l' utilizzo richiudere accuratamente la confezione, poiché l' evaporazione del solvente porta all' essiccazione del prodotto.

Per macchie più antiche e profonde continuare ad applicare Stain Out, fino alla rimozione completa della macchia.



ETICHETTATURA e SICUREZZA

Stain Out è un prodotto chimico.
Per informazioni sull' etichettatura e i rischi connessi alla manipolazione e all'uso del prodotto consultare la Scheda di Sicurezza. Se non è stata ricevuta, essa è disponibile a richiesta presso Industrial Chem Italia.

STOCCAGGIO

Stain Out chiuso e sigillato nei suoi contenitori originali, conservato a una temperatura tra i 5 e i 30 °C lontano da fonti di calore e protetto dalla luce solare diretta, ha una durata di 12 mesi.

RESPONSABILITA'

Tutte le informazioni e raccomandazioni qui contenute, sono basate su informazioni e test che riteniamo attendibili; non conoscendo tuttavia le condizioni circa i materiali trattati e le modalità di messa in opera in cui il prodotto viene utilizzato, si declina ogni responsabilità circa l'adeguatezza del prodotto per ogni particolare applicazione. È infatti compito dell'utilizzatore verificare, sotto la propria responsabilità, se il prodotto descritto si presta in maniera appropriata all'uso a cui è destinato, e di procedere a tutte le prove preliminari necessarie, comprese quelle legate all'utilizzo di macchine o strumenti di lavoro.

rev. settembre 2021



INDUSTRIAL CHEM ITALIA s.r.l.
www.industrialchemitalia.com
Tel. +39 0584 969 607
commerciale@industrialchemitalia.com

AZIENDA CON
SISTEMA DI GESTIONE
CERTIFICATO DA DNV
ISO 9001 • ISO 14001

Stain Out

oil and grease stain remover

technical shee

PROPERTIES

- Stain Out is a special formulation which, thanks to its action, penetrates the stained natural stone and removes stains of grease, wax, mineral and vegetable oil.
- Stain OutStain Out is easy to use, absorbs stains in minutes and removes them.
- Stain Out does not leave halos and does not alter the color of the treated materials.
- It is possible to perform localized applications of the product thanks to its creamy formulation.

APPLICATION FIELD

Stain Out is suitable for all polished, unpolished, smooth, rough, patinated, etc. surfaces. It is suitable for all types of stone materials, terracotta, concrete, etc.

INSTRUCTION FOR USE

Shake well before use.

- Apply Stain Out on the stain, covering it entirely, creating a layer of product of at least 5 mm.
- If needful, cover the surface with plastic film.
- Leave to dry until the surface becomes dry and cracked
- Remove the residue with a brush.
- Repeat the operation if needed

USEFUL RECOMMENDATIONS

After use, close the can carefully. Stain Out evaporates and dries very quickly.

For older and deeper stains continue to apply Stain Out until the stain is completely removed.

SAFETY & LABELING

Stain Out is a chemical product.
For information concerning labeling, handling and utilization risks , please read the Material Safety Data Sheet. If this has not been received, it can be requested to Industrial Chem Italia.

STORAGE

Stain Out properly stored in the original unopened containers, at a temperature between 5 - 30°C, far from direct sunlight and other heat sources has a shelf life of 12 months.

RESPONSIBILITY

All the data and recommendations hereby contained, are based on reliable tests and informations. However being unaware of the conditions of the materials that are going to be treated as well as the modalities of application that are going to be used, our company doesn't assume any kind of resposability. It is up to the user to determine, under its full responsibility, whether this specific product is suitable for the proposed use and to perform all preliminary tests, including those related to the use of machines and tools.



rev. september 2021



INDUSTRIAL CHEM ITALIA s.r.l.
www.industrialchemitalia.com
Tel. +39 0584 969 607
export@industrialchemitalia.com

COMPANY WITH
MANAGEMENT SYSTEM
CERTIFIED BY DNV
ISO 9001 • ISO 14001